

VW-300PRO

Single Wheel Vibratory Roller, Hand Guided

PRODUCT-INFORMATION

Technical Data

VW-300PRO

Engine / Drive	4-stroke-OHV-petrol engine LONCIN G200F	
Engine power	kW	4,1 at 3.600 rpm
Displacement	cm ³	196
Gasoline	Liter	3,6 / ROZ95
Engine oil	Liter	0,6 / SAE 10W-30/40
Starting	Recoil starter	
Working width	mm	600
Driving speed / forward	km/h	0 – 2,1 max.
/ reverse	km/h	0 – 1,4 max.
Climbing capability, max.	%	20
Driving system	hydrostatic	
Excitation system drive type	Mechanic	
Frequency	Hz	72
Amplitude	mm	0,6
Force	kN	13,5
Water tank volume	l	16
Oil tank volume	ml	50 / CF-4 20W/50
Sound power level	LWA	108 dB(A)
Static line load	kg/cm	4,4
Deadweight	kg	ca. 266
Shipping weight (net / gross)	kg	ca. 262/312
Packaging dimensions (LxWxH)	mm	870x770x1220

innovative gearbox
 „Made in Japan“



Art. No.: VW300PRO

EAN: 40 47424 00699 3

Equipment Features:

The VW-300PRO vibratory roller is suitable for small compaction jobs, such as road construction, gardening and landscaping, paving or small repair jobs in road construction.

- Stepless hydrostatic drive: forward 0-2.1 km/h, reverse 0-1.4 km/h
- Low lateral protrusion allows optimal compaction up to walls or curbs
- Scrapers front and rear
- Robust protective frame with central single-point suspension
- Safety supports front and rear
- Guide drawbar can be positioned vertically for transport
- Overhead water tank ensures constant water sprinkling for blacktop work

