

# RP-i12

## Forward moving compactor plate

### PRODUCT-INFORMATION

#### Technical Data

#### RP-i12

Engine / Drive	4-stroke-OHV petrol engine LONCIN G200F	
Engine power	kW	4,1 at 3.000 rpm
Displacement	cm <sup>3</sup>	196
Gasoline tank volume	Liter	3,6 / ROZ 91 or higher
Engine oil tank volume	Liter	0,6 / SAE 10W-30/40
Plate dimensions (LxW)	mm	500 x 370
Frequency	Hz	70
Force	kN	10,5
Surface performance	m <sup>2</sup> /h	450
Max. Feeding rate	m/min	20
Vibrating impacts	VPM	5600
Compaction depth	cm	20
Sound power level	L <sub>WA</sub>	108 dB(A)
Deadweight	kg	ca. 73,7
Shipping weight (net)	kg	ca. 80
Packaging dimensions (L/W/H)	mm	750 / 380 / 610

Clear rubber mat,  
wheel set and water  
tank included



Art. No.: RPi12

EAN: 40 47424 00667 2



Water tank



transport wheels

#### Equipment Features:

- The forward running vibratory plate is particularly suitable for paving work, repair work in path construction, gardening and landscaping.
- The water sprinkler is indispensable when compacting very dusty substrates, as well as for all asphalt and tar work! A nozzle pipe distributes the water in front of or under the slab. The water quantity is adjustable and the tank is removable.
- Foldable handle - compact size for transport and storage.
- Protective grille on exhaust, handle damped against vibration.
- Rugged, durable base plate for extra precision work.
- Equipped with V-belt protected on all sides,
- protective frame and transport chassis.

rubber mat opt. available (EAN: 4047424002995 / Art.No.: 5TGRP75)