

STM 350-1200PRO

Professional stone cutting saw

PRODUCT-INFORMATION

Technical Data

STM 350-1200PRO

Operating voltage	230 V / 50 Hz
Motor power	2,0 kW
Idle speed	2500 rpm
Operating current	16 A
Protection class	IP 54
Dimensions (LxWxH)	1460 x 770 x 1500 mm
Table size	1150 x 510 mm
Diamond cutting disc	Ø 350 x 30 mm
Working speed	80 m/s
Max. cutting depth	107 mm
Max. cutting height	1200 mm
Tilt angle	0 – 45°
Volume water tray	32,0 l
Sound pressure level LPA	72 dB(A)
Sound power level LWA	85 dB(A)
Weight (net / gross)	129 / 151 kg
Packaging dimensions	1600 / 750 / 800 mm



Art. No.: STM3501200PRO

EAN: 40 47424 00987 1



Equipment Features:

The particularly robust STM350-1200PRO stone cutting machine is versatile, suitable for cutting porcelain stoneware, granite, clinker, marble, terrazzo, natural stone and concrete block.

- Equipped with a max. cutting length of 1200 mm, especially for large-format workpieces.
- Designed as a bridge head saw, the STM 350-1200PRO has a pivoting cutting bridge for optimal miter cuts from 0° to 45° and a lowerable head for cross-cuts
- Robust frame with metal tray and maintenance-free submersible pump for pumping cooling water
- Convenient and easy transport thanks to transport wheels and handles (retractable), foldable feet
- Incl. segmented diamond cutting disc Ø 350 x 30 mm for wet cutting

Optional accessories (not included):

- Diamond-TS segm. Ø 350x30mm (Art. No. DS350S, EAN: 40 47424 00091 5)
- Diamond -TS closed Ø 350x30mm (Art. No. DS350G, EAN: 40 47424 00092 2)
- Diamond -TS Turbo Ø 350x30mm (Art. No. DS350T, EAN: 40 47424 00093 9)