

PRODUCT-INFORMATION

PROFI-Log Splitter with 3-point hitch/PTO or combination drive

Technical Data	HZ-22	HEZ-22	HZ-30	HEZ-30
Drive	PTO Gearbox	Electric Motor 5,1 kW S6 40% 400V and PTO / 3-point hitch	PTO / 3-point hitch	Electric Motor 5,5 kW S6 40% 400V and PTO / 3-point hitch
Splitting force max.	22t ±10%	22t ±10%	30t ±10%	30t ±10%
Splitting stroke	94,8 cm	94,8 cm	94,8 cm	94,8 cm
Splitting length	560 - 1100 mm	560 - 1100 mm	560 - 1100 mm	560 - 1100 mm
Splitting diameter -Ø	80 – 350 mm	80 – 350 mm	80 – 400 mm	80 – 400 mm
Hydraulic pressure max.	27,5 MPa	27,5 MPa	26,0 MPa	26,0 MPa
Hydraulic oil tank volume	24,0 Liter	24,0 Liter	30,0 Liter	30,0 Liter
3-point hitch	Cat. I + II	Cat. I + II	Cat. I + II	Cat. I + II
PTO Speed	540 1/min	540 1/min	540 1/min	540 1/min
Tractor power	20 PS	20 PS	20 PS	20 PS
Working speed	4,3 / 10,5 cm/s	4,3 / 10,5 cm/s	3,7 / 12,5 cm/s	3,7 / 12,5 cm/s
Return speed	7,5 cm/s	7,5 cm/s	6,7 cm/s	6,7 cm/s
Dimensions	110 x 150 x 250 cm	110 x 150 x 250 cm	110 x 150 x 250 cm	110 x 150 x 250 cm
Weight (net / gross)	287,0 / 299,0 kg	345,1 / 357,3 kg	338,4 / 351,4 kg	397,4 / 410,0 kg
Packaging Dimension (LxWxH)	94 x 68 x 200 cm	94 x 68 x 200 cm	97 x 68 x 200 cm	97 x 68 x 200 cm
Art. No.	HZ22	HEZ22	HZ30	HEZ30
EAN	40 47424 00911 6	40 47424 00912 3	40 47424 00982 6	40 47424 00913 0
5HSW winch(1), optional	-	Yes	-	Yes
5HSW2 winch(2), optional	Yes	-	Yes	-

Equipment Features:

- Vertical hydraulic splitter with power take-off or combination drive
- Sturdy frame and robust splitting wedge
- 2 splitting speeds & reverse as standard
- Adjustable splitting stroke
- Cylinder can be lowered for transport and storage
- Mechanical 2-hand operation
- Depth adjustment for fatigue-free working
- With 3-point hitch (Cat. I+II)
- All models with mechanical log pick-up
- Transport wheels
- NEW also available with hydraulic winch for
- Model with PTO available

Accessoires (optional):

Winch (1), hydraulic for **HEZ-22 and HEZ-30**

(Art. No. 5HSW, EAN: 40 47424 00708 2)

Winch (2), hydraulic for **HZ-22 and HZ-30**

(Art. No. 5HSW2, EAN: 40 47424 00915 4)

According to the standard, a winch may only be mounted on a log splitter if it is mounted on a tractor!

