

# LVS-30GX

*Tamping rammer with Honda engine*

## PRODUCT-INFORMATION

### Technical Data

### LVS-30GX

Engine / Drive	4-stroke- petrol engine Honda GX35
Engine power	1.0 kW at 7000 1/min
Displacement	38,5 cm <sup>3</sup>
Tank volume	0,63 Liter
Engine oil volume	0,1 Liter
Starting	Recoil
Compacting pressure	9,1 kN
Stroke up to	50 mm
Stamping foot width	135 mm
Stroke rate, max.	790 1/min
Gar. Sound power level L <sub>WA</sub>	106 dB(A)
Weight (net / gross)	32 / 36 kg
Packaging dimensions (L/W/H)	925 / 325 / 600 mm



Art. No.: LVS30GX

EAN: 40 47424 00704 4



### Equipment Features:

The LUMAG LVS 30-GX rammer is ideal for working in confined areas. The slim design and narrow tamping foot guarantee more compaction comfort even in narrow trenches.

- Lightweight tamper with extra narrow foot for compacting pipe spandrels and very narrow trenches
- Also ideal for compacting edge areas of walkways, cable laying and small patching jobs
- Integrated motor protection frame and cover
- Handles for easy transport
- Equipped with a powerful Honda GX 35 4-stroke gasoline engine